



HMS NETWORKS ANYBUS WIRELESS

AWB2031-B

Wireless Bolt Ethernet RJ45 PoE white

- Connect any industrial machinery to a wireless network
- IP rated - suitable for most industrial environments
- For wall or hole mounting
- WIFI / Bluetooth
- Range of up to 400m



PRODUCT DESCRIPTION

Anybus Wireless Bolt is able to connect industrial machines and devices to a wireless network. It can be attached onto a cabinet or a machine to enable wireless access over Bluetooth®, Bluetooth Low Energy® or Wireless LAN (WiFi).

The Anybus Wireless Bolt can also communicate over Industrial Ethernet and supports protocols such as BACnet/IP, PROFINET, EtherNet/IP, Modbus TCP as well as all TCP and UDP based protocols.

The bolt is used as a wireless access point to connect industrial machines/ devices to a wireless network, it can also be used to wirelessly connect machines and devices to a factory network. The Anybus Wireless Bolt comes as an All-in-one package including: connector, communication processor and integrated antenna within the same unit, with an IP67 rating which makes it ideal for most industrial environments. The wireless bolt has a range of up to 100m via bluetooth or WIFI and allows you to use your own devices (laptop/ tablet/ smartphone) as an HMI. The bolt can be mounted to a cabinet or machine an M50 screw.

Wireless Bolt key features:

- Wirelessly configure/ troubleshoot industrial machinery
- IP67 rating - Designed for harsh environments
- Connects to your own devices via bluetooth or Wireless LAN - Eliminate the need for HMIs
- Can be powered over Ethernet or 3-pole 19-36VDC connector
- High speed internet connection via LTE (4G)
- Up to 100m range

The Anybus Wireless Bridge II can be used to create an industrial wireless connection in an industrial ethernet network and it can also be used as an access point. The wireless Bridge II is ideal for hard to reach areas or hazardous areas where cables are not desirable; the Wireless Bridge II tends to be paired with a second Wireless Bridge II to replace cables. The wireless bridge has a range of up to 400m and is IP65 rated. The Anybus Bolt and Wireless Bridge II are both fully compatible with each other and can be used to extend a wireless network.

Wireless Bridge II key features:

- Industrial ethernet cable replacement via Bluetooth or WIFI
- Can also be used as an access point for up to 7 clients
- No programming required to set up
- Supports industrial Ethernet protocols such as EtherNet/IP, Modbus TCP, PROFINET, BACnet/Ip
- Up to 400m range

TECHNICAL DATA

TECHNICAL DATA

Height	75 mm
Width	68 mm
Voltage dc max	30 V

Voltage dc min	9 V
Temperature operational max	65 °C
Connection antenna	One internal antenna. Dual band 2.4GHz and 5GHz
Temperature operational min	-40 °C
Power consumption	1,7 W