

INSULATED RING TERMINALS

QKS

2534.0

QKS 1, 1mm² Ring crimp, M4, Red

- Ring shape complies with DIN 46237
- Cu-ETP acc. to DIN EN13599, soldered, galv, Sn
- Wide easy entry collar PA insulation
- Continuous-use temperature range -55°C...105°C



PRODUCT DESCRIPTION

Conta-Clip offer a range of standard automotive type insulated ring crimp terminals to suit many applications.

These terminals are usually identified by the coloured collars for the various cable sizes.

The standard range covers from 0.5mm² to 6mm² cable sizes with M4 to M8 connections.

All types within the range have a widened cable entry, making for an easy installation.

TECHNICAL DATA

GENERAL DATA

Colour	Red
Rated wire cross section to (AWG)	18
Rated wire cross section from (AWG)	20
Ring hole diameter	4,3 mm
Conductor shape	Ring shape acc.DIN 46237
Cross section max	1 mm ²
Cross section min	0,5 mm ²

DIMENSIONS

Width of ring	8 mm
---------------	------

Diameter of feed-in funnel	4,1 mm
Length to middle of ring	18 mm
DIN size	A 4 - 1

MATERIALS

Operating temperature from	-55 °C
Operating temperature to	105 °C
Soldered	Yes
Conductor material	Copper
Contact surface	Tinned

APPROVALS

DIN approvals	EN 13599
---------------	----------

ADDITIONAL DATA

Pack size	100
Country of origin	TW
Tariff code	85369010
Weight	0,82 g
Insulation material	Expanded PA

