

INSULATED BUTT TERMINALS

STV, STV HS

3074.0

STV 1, 1mm² Insulated joint/butt crimp, Red

- Cu-ETP acc. to DIN EN13600, galv, Sn
- Wide easy entry collars PVC insulation
- Continuous-use temperature range -10°C...75°C
- Heat shrink waterproof versions



PRODUCT DESCRIPTION

Conta-Clip offer a range of standard automotive type insulated joining/butt crimp terminals to suit many applications.

These terminals are usually identified by the coloured collars for the various cable sizes.

The standard range covers from 0.5mm² to 6mm² cable sizes.

All types within the range have a widened cable entry, making for an easy installation.

The HS versions have a double layer of insulation and combined adhesive heat shrink to give a waterproof joint for the harshest applications.

TECHNICAL DATA

GENERAL DATA

Colour	Red
Rated wire cross section to (AWG)	16
Rated wire cross section from (AWG)	20
Cross section max	1,5 mm ²
Cross section min	0,5 mm ²

DIMENSIONS

Diameter of feed-in funnel	4,1 mm
Length	26 mm
DIN size	1

MATERIALS

Operating temperature from	-10 °C
Operating temperature to	75 °C
Soldered	No
Conductor material	Copper
Contact surface	Tinned

APPROVALS

DIN approvals	EN 13600
---------------	----------

ADDITIONAL DATA

Pack size	100
Country of origin	TW
Tariff code	85369010
Weight	1,17 g
Insulation material	Expanded PVC

