

UNINSULATED PIN TERMINALS - SKS

SKS

30881.0

SKS 1/U, 1mm² pin-shaped cable lug

- Pin crimps for cable size 0.5 mm² to 95 mm²
- Pin shaped acc. to DIN 46230 and similar
- Cu-ETP acc. to DIN EN13599, soldered, galv. Sn
- Heat resistant to +125 °C



PRODUCT DESCRIPTION

Conta-Clip have a range of tin-plated copper un-insulated pin crimp lugs (DIN 46230) that range from 1mm² up to 95mm².

This range has an operating temperature of up to 125°C and conform to DIN EN13599.

TECHNICAL DATA

GENERAL DATA

Colour	Natural
Rated wire cross section to (AWG)	18
Rated wire cross section from (AWG)	20
Conductor shape	Pen shape acc.DIN 46230
Cross section max	1 mm ²
Cross section min	0,5 mm ²

DIMENSIONS

Length	18,3 mm
Stripping length	5 mm
Length of feed-in funnel	5 mm

MATERIALS

Operating temperature to	125 °C
Soldered	Yes
Conductor material	Copper
Contact surface	Tinned

APPROVALS

DIN approvals	EN 13599
----------------------	----------

ADDITIONAL DATA

Pack size	100
Country of origin	TW
Tariff code	85369010
Weight	0,67 g

