

STL 1550

11877.1

STL 1550/3.5/2V 2P PCB VERT

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Type	Header
Pitch	3,5 mm
Colour	Green
Number of poles	2
Approvals	UL, cUL, VDE

RATINGS

Rated current	10 A
Rated voltage	160 V
Rated impulse voltage	2,5 kV
Overvoltage category	III
Contamination degree	3

DIMENSIONS

Length	7 mm
Width	8,4 mm
Height	9,2 mm
Width left	2,45 mm
Width right	2,45 mm
Drillhole diameter	1,2 mm
Diameter of the connection pin	0,8 mm

Length of pin	3,4 mm
---------------	--------

CONNECTION DATA

Connector type/principle	Pin header
Connector version	Fixed
Number of plugin rows	1

MATERIALS

Housing material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-30 °C
Operating temperature to	105 °C
Contact pin	Copper alloy

APPROVALS

UL test standard	UL 1059
Rated voltage UL	300 V
Rated current UL	10 A
cUL test standard	CSA 22.2 No.158
Rated voltage cUL	300 V
Rated current cUL	10 A
VDE test standard	DIN EN 61984
Rated voltage VDE	160 V
Rated current VDE	10 A

ADDITIONAL DATA

Glow wire ignition temperature (GWIT)	GWIT 775
Insulation resistance	$1 \cdot 10^{13} \Omega \times \text{cm}$
Recommended wave soldering temperature	265 °C
Pack size	50
Country of origin	QU
Tariff code	85366990
Glow wire flammability index (GWFI)	GWFI 850
Angle circuit board / contact	90° (vertically upwards)
Weight	0,4 g
Recommended wave solder duration min	3 s

GWFI after-glow time	30 s
Plug-in cycles acc. to standard	100
GWIT exposure time	5 s
Recommended wave solder duration max	4 s
Current creepage resistance	CTI 600

