

**PZK 3750**

13334.1

PZK 3750/2/5,00 GN

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Type	Double-level PCB terminal
Pitch	5 mm
Colour	Green
Number of poles	2
Approvals	UL, cUL, VDE

**RATINGS**

Rated current	12 A
Rated voltage	250 V
Rated cross section	2,5 mm <sup>2</sup>
Rated impulse voltage	2 kV
Overvoltage category	III
Contamination degree	3

**DIMENSIONS**

Length	21 mm
Width	11,7 mm
Height	25,7 mm
Width left	3,7 mm
Width right	3 mm
Drillhole diameter	1,3 mm

Diameter of the connection pin	0,7 mm
Length of pin	4 mm

## CONNECTION DATA

Connector type/principle	Spring clamp
Number of levels	2
Angle of PCB/wire connection	45°/135° (diagonally upwards)
Type of attachment to PCB	Connecting contact
Electrical connection type to PCB	Solder
Cross section single wire from	0,08 mm <sup>2</sup>
Cross section single wire to	2,5 mm <sup>2</sup>
Cross section stranded wire from	0,14 mm <sup>2</sup>
Cross section stranded with ferrule to	1,5 mm <sup>2</sup>
Cross section stranded wire to	2,5 mm <sup>2</sup>
Cross section stranded with ferrule from	0,14 mm <sup>2</sup>
Rated wire cross section to (AWG)	14
Rated wire cross section from (AWG)	28
Stripping length	6 mm

## MATERIALS

Housing material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-30 °C
Operating temperature to	105 °C
Main spring	Stainless steel
Solder lug	Copper alloy

## APPROVALS

UL test standard	UL 1059
Rated voltage UL	300 V
Rated current UL	16 A
cUL test standard	CSA 22.2 No.158
Rated voltage cUL	300 V
Rated current cUL	16 A
VDE test standard	DIN EN 60998
Rated voltage VDE	250 V

Rated current VDE	12 A
-------------------	------

## ADDITIONAL DATA

Glow wire ignition temperature (GWIT)	GWIT 775
Insulation resistance	$1 \cdot 10^{13} \Omega \times \text{cm}$
Recommended wave soldering temperature	265 °C
Pack size	50
Country of origin	QU
Tariff code	85369010
Glow wire flammability index (GWFI)	GWFI 850
Weight	5,1 g
Recommended wave solder duration min	3 s
GWFI after-glow time	30 s
GWIT exposure time	5 s
Recommended wave solder duration max	4 s
Current creepage resistance	CTI 600
Connection cycles acc. to standard	10

