

PK 601

14123.1

PK 601/2/3,50-V GN

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Type	PCB terminal
Pitch	3,5 mm
Colour	Green
Number of poles	2
Approvals	UL, cUL, VDE

RATINGS

Rated current	10 A
Rated voltage	130 V
Rated cross section	1 mm ²
Rated impulse voltage	1,25 kV
Overvoltage category	III
Contamination degree	3

DIMENSIONS

Length	7,4 mm
Width	7,4 mm
Height	8,5 mm
Width left	2,15 mm
Width right	1,75 mm
Drillhole diameter	1,2 mm

Diameter of the connection pin	0,9 mm
Length of pin	3,8 mm

CONNECTION DATA

Connector type/principle	Screw
Number of levels	1
Angle of PCB/wire connection	0°/180° (horizontal)
Type of attachment to PCB	Connecting contact
Electrical connection type to PCB	Solder
Cross section single wire from	0,08 mm ²
Cross section single wire to	1,5 mm ²
Cross section stranded wire from	0,08 mm ²
Cross section stranded with ferrule to	0,34 mm ²
Cross section stranded wire to	1 mm ²
Cross section stranded with ferrule from	0,14 mm ²
Rated wire cross section to (AWG)	16
Rated wire cross section from (AWG)	28
Stripping length	6 mm
Screw size	M 2
Torque	0,2 Nm

MATERIALS

Housing material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-30 °C
Operating temperature to	105 °C
Solder lug	Brass
Screw material	Steel
Clamp material	Brass

APPROVALS

UL test standard	UL 1059
Rated voltage UL	150 V
Rated current UL	10 A
cUL test standard	C22.2 No 158
Rated voltage cUL	150 V

Rated current cUL	10 A
VDE test standard	DIN EN 60998
Rated voltage VDE	130 V
Rated current VDE	10 A

ADDITIONAL DATA

Glow wire ignition temperature (GWIT)	GWIT 775
Insulation resistance	$1 \cdot 10^{13} \Omega \times \text{cm}$
Recommended wave soldering temperature	265 °C
Pack size	50
Country of origin	QU
Tariff code	85369010
Glow wire flammability index (GWFI)	GWFI 850
Weight	0,87 g
Recommended wave solder duration min	3 s
GWFI after-glow time	30 s
GWIT exposure time	5 s
Recommended wave solder duration max	4 s
Current creepage resistance	CTI 600
Connection cycles acc. to standard	5

