

## ISTLZ 950

14150.1  
ISTLZ 950/2/5,08-H GN



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Type	Inverted header
Pitch	5,08 mm
Colour	Green
Number of poles	2
Approvals	UL, cUL, VDE

#### RATINGS

Rated current	12 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Overvoltage category	III
Contamination degree	3

#### DIMENSIONS

Length	19 mm
Width	12,16 mm
Height	8,5 mm
Width left	3,54 mm
Width right	3,54 mm
Drillhole diameter	1,4 mm
Diameter of the connection pin	1,05 mm

Length of pin	3,5 mm
---------------	--------

## CONNECTION DATA

Connector type/principle	Pin header
Connector version	Fixed
Number of plugin rows	1

## MATERIALS

Housing material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-30 °C
Operating temperature to	105 °C
Contact spring	Bronze

## APPROVALS

UL test standard	UL 1059
Rated voltage UL	300 V
Rated current UL	10 A
cUL test standard	CSA 22.2 No.158
Rated voltage cUL	300 V
Rated current cUL	10 A
VDE test standard	DIN EN 61984
Rated voltage VDE	250 V
Rated current VDE	12 A

## ADDITIONAL DATA

Glow wire ignition temperature (GWIT)	GWIT 775
Insulation resistance	$1 \cdot 10^{13} \Omega \times \text{cm}$
Recommended wave soldering temperature	265 °C
Pack size	50
Country of origin	QU
Tariff code	85366990
Glow wire flammability index (GWFI)	GWFI 850
Angle circuit board / contact	0°/180° (horizontal)
Weight	1,61 g
Recommended wave solder duration min	3 s

<b>GWFI after-glow time</b>	30 s
<b>Plug-in cycles acc. to standard</b>	100
<b>GWIT exposure time</b>	5 s
<b>Recommended wave solder duration max</b>	4 s
<b>Current creepage resistance</b>	CTI 600

