



PKDR 2,5

5204.3

PKDR 2,5/4/5,00 OG



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Type	Double-level PCB terminal
Pitch	5 mm
Colour	Orange
Number of poles	4
Approvals	CSA

RATINGS

Rated current	13 A
Rated voltage	250 V
Rated cross section	2,5 mm ²
Rated impulse voltage	4 kV
Overvoltage category	III
Contamination degree	3

DIMENSIONS

Width	17,5 mm
Height	35,5 mm
Width left	2,5 mm
Width right	5 mm
Drillhole diameter	1,3 mm
Diameter of the connection pin	1 mm

CONNECTION DATA

Connector type/principle	Screw
Number of levels	2
Angle of PCB/wire connection	0°/180° (horizontal)
Type of attachment to PCB	Connecting contact
Electrical connection type to PCB	Solder
Cross section single wire from	0,2 mm ²
Cross section single wire to	4 mm ²
Cross section stranded wire from	0,2 mm ²
Cross section stranded with ferrule to	2,5 mm ²
Cross section stranded wire to	2,5 mm ²
Cross section stranded with ferrule from	0,2 mm ²
Rated wire cross section to (AWG)	14
Rated wire cross section from (AWG)	24
Stripping length	7 mm
Screw size	M 2,5
Torque	0,6 Nm

MATERIALS

Housing material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-30 °C
Operating temperature to	105 °C
Solder lug	Copper
Screw material	Steel
Clamp material	Steel

APPROVALS

CSA test standard	CSA 22.2 No.158
Rated voltage CSA	300
Rated current CSA	20 A

ADDITIONAL DATA

Glow wire ignition temperature (GWIT)	GWIT 775
Insulation resistance	1*10 ¹² Ω x cm
Recommended wave soldering temperature	265 °C

Pack size	50
Country of origin	DE
Tariff code	85369010
Glow wire flammability index (GWFI)	GWFI 960
Weight	9,6 g
Recommended wave solder duration min	3 s
GWFI after-glow time	30 s
GWIT exposure time	5 s
Recommended wave solder duration max	4 s
Current creepage resistance	CTI 600

