


## ULTRA FLAT STAINLESS STEEL

Progress® ultraFLAT A2, Progress® ultraFLAT  
A2 HT

1040.17.96.30.065

Gland stainless steel A2 ultraFLAT, EHEDG, M16, ø5...  
6.5mm

- Flush fitting
- A2 - AISI 303
- FKM seals (FDA approved) or FPM seals
- EHEDG certified for the food industry
- IP68 up to 10 bar, IP69



### PRODUCT DESCRIPTION

The Progress® ultraFLAT A2 is a stainless steel flush mount cable gland designed application areas such as:

- Clean rooms
- Food industry
- Anti-vandalism
- Aesthetic design
- High temperature applications -40°C to +200°C

The ultra-flat construction of the Progress® ultraFLAT cable gland prevents any manipulation from the outside. No external nut is visible on the external side of the gland.

In addition, the cable gland has been designed with an attractive shape, which is less industrial looking and more 'design' friendly to the eye.

The Progress® ultraFLAT cable gland offers very little surface trap points for contamination, so is ideally suited for wash down environments, which is crucial for cleanroom and food applications. These food EHEDG certified glands are easily recognised, as they have a blue coloured FKM seal which have been cleared by the FDA.

# TECHNICAL DATA

## GENERAL DATA

Thread Size (G)	M16
Insert Type	One-Piece
Cable diameter min	5 mm
Cable diameter max	6,5 mm
IP class	IP 68 (up to 10 bar), IP 69 further protection

## DIMENSIONS

Thread pitch	1,5
Thread length	21 mm
Height (H)	4 mm
Spanner width (AF)	19 mm
External diameter (□A)	22 mm
Wall thickness	5 mm max.

## MATERIALS

Material	Stainless steel A2
Material of seals	FKM
Inner-nut material	Nickel-plated brass
Sealing washer material	FKM
Temperature range	-40°C ... +200°C

## APPROVALS

Approvals	CE
Strain relief	Version A acc. to EN 62444
Certificate	EHEDG

## ADDITIONAL DATA

Pack size	25
Country of origin	CH
Tariff code	74199949
Weight	34,28 g

