


90° ELBOW GLANDS AND 45°/90° ELBOWS

Progress® Elbow

5200.12
Gland NPB, 90° elbow, M12, ø5...6.5mm

- Nickel plated brass
- Ideal for tight spaces
- thread adaptor versions
- -40°C...+100°C
- up to IP68



PRODUCT DESCRIPTION

The popular Progress® range of nickel-plated brass are also available with 90° elbow, so ideal for tight spaces.

In addition to the glands, there are also a range of 90° and 45° elbows with internal & external threads to give additional flexibility.

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M12
Insert Type	One-Piece
Cable diameter min	5 mm
Cable diameter max	6,5 mm
IP class	IP 68

DIMENSIONS

Thread pitch	1,5
Thread length	8 mm
Height (H)	27 mm
Spanner width (AF)	15 mm
Width (B)	32 mm
Centres (A)	11 mm

MATERIALS

Material	Nickel-plated brass
Material of seals	TPE
Temperature range	-40°C ... +100°C

APPROVALS

Approvals	SEV, CE, DNV, EAC, VDE
Strain relief	Version A acc. to EN 62444
Entry thread IP class	IP 68, if entry thread is sealed

ADDITIONAL DATA

Pack size	50
Country of origin	CH
Tariff code	74199949
Weight	24,08 g

