


SPECIAL ENTRY

Progress® Special entry and IG

1100.17.50
Gland NPB, M16, extra long, ø6...10.5mm

- 50mm and 100mm thread lengths
- Custom sizes on request
- -40°C...+100°C
- IP68 up to 10 bar, IP69



PRODUCT DESCRIPTION

The Progress® special entry range of nickel-plated brass glands is ideal for applications where a longer thread is required.

They come as standard with 50mm & 100mm lengths, but Agro can also offer custom made solutions to give the maximum flexibility for your cable entry requirements.

The outstanding compression technology is designed to be used in a wide range of applications and guarantees an effective seal with excellent cable-protecting strain relief, even where vibration is an issue.

When tightening the gland, a small bulge in the sealing insert confirms the correct tightening torque has been reached, giving positive visible feedback to the installer.

The integrated retaining grooves in the lower part of the gland and in the sealing insert prevent the insert from twisting and becoming deformed.

Agro can also offer a range of special entry glands with internal threads (Progress® IG) which can be coupled directly on threaded tubing. Please contact us for further information.

TECHNICAL DATA

GENERAL DATA

Cable diameter inner max	8 mm
Cable diameter min	8 mm
Cable diameter inner min	6 mm
Thread Size (G)	M16
Cable diameter max	10,5 mm
IP class	IP 68 (up to 10 bar) IP 69 further protection
Insert Type	Two-Piece

DIMENSIONS

Thread pitch	1,5
Height (H)	22 mm
Spanner width (AF)	24 mm
Useable thread length (L1)	40 mm
Thread length	50 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	NBR
Material of seals	TPE
Temperature range	-40°C ... +100°C

APPROVALS

Strain relief	Version A acc. to EN 62444
Approvals	SEV, CE, DNV, EAC, VDE

ADDITIONAL DATA

Pack size	10
Country of origin	CH
Tariff code	74199949
Weight	74,8 g