

## COMBINATION CONDUIT GLANDS EX E II

Progress® Kombi EX

EX1700.12.10.065  
Combi gland Ex NPB, Ex e II, M12 - ø10mm, ø4...  
6.5mm

- IECEx certified
- Suitable for metal/braided conduits only
- IP66/68
- Long thread available on request
- -60°C...+100°C



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Cable diameter min	4 mm
Thread Size (G)	M12
Cable diameter max	6,5 mm
IP class	IP 66 / IP 68
Insert Type	One-Piece

#### DIMENSIONS

Thread pitch	1,5
Height (H)	33 mm
Spanner width (AF)	17 mm
Thread length	5 mm
Conduit diameter (AD)	10mm

#### MATERIALS

Material	Nickel-plated brass
Materials O-ring	FPM

<b>Material of seals</b>	TPE
<b>Temperature range</b>	-60°C ... +100°C

## APPROVALS

<b>Ex-Zone gas</b>	II 2G Ex eb IIC Gb
<b>Test standard</b>	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
<b>Ex zones</b>	Gas 1 and 2 / dust 21 and 22
<b>IECEX certificate</b>	IECEX SEV 15.0019X
<b>EX-zone dust</b>	II 2D Ex tb IIIC Db
<b>Certificate</b>	SEV 15 ATEX 0152X
<b>Approvals</b>	CE, EX, IECEX

## ADDITIONAL DATA

<b>Pack size</b>	50
<b>Country of origin</b>	CH
<b>Tariff code</b>	74199949
<b>Weight</b>	25,4 g