

EMC EASYCONNECT EX E II

Progress® MS EMC easyCONNECT Ex e II

EX1803.83.12.065
Gland Ex EMC easyCONNECT NPB, Ex e II, clamped,
M12, ø5...6.5mm



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Cable diameter min	5 mm
Thread Size (G)	M12
Cable diameter max	6,5 mm
IP class	IP 66 / IP 68
Insert Type	One-Piece

DIMENSIONS

Thread pitch	1,5
Height (H)	31 mm
Spanner width (AF)	16 mm
Thread length	5 mm

MATERIALS

Material screw	Stainless steel A2
Material	Nickel-plated brass
Materials O-ring	FPM
Material insert	TPE
Temperature range	-60°C ... +100°C

APPROVALS

Ex-Zone gas	II 2G Ex eb IIC Gb
Test standard	IEC 60079-0 / IEC 60079-7 / IEC 60079-31
Ex zones	Gas 1 and 2 / dust 21 and 22
IECEX certificate	IECEX SEV 15.0018
EX-zone dust	II 2D Ex tb IIIC Db
Certificate	SEV 15 ATEX 0151
Approvals	CE, EX, IECEX

ADDITIONAL DATA

Pack size	50
Country of origin	CH
Tariff code	74199949
Weight	27,7 g