

MINIMOTOR - PCEF WORM GEARED MOTOR WITH FURTHER PLANETARY GEAR

PCEF4T2B3-10

- For clean environments
- IP67 as standard
- Up to 90Nm rated torque
- Minimal dirt trap points
- Epoxy coated with no external fan



PRODUCT DESCRIPTION

White epoxy coating for increased protection against chemicals and harsh working environments.
IP67 rated with no external fan.


MOTOR: Asynchronous single or three phase with 2 poles, totally enclosed. Thermal safety feature. Class H winding.

GEAR UNIT: Die-cast aluminium casing in the first reduction stage, with worm screw and steel casing in the second planetary stage, with three internal planetary gears. Wheel rim in bronze 120-160 HB hardness. Hardened steel screw with ground threads rotating on ball and roller bearings. Output shaft available in stainless steel upon request.

Lubrication with special long life oil. Sealing rings made in special rubber for high temperatures. . Rated torque 90 Nm. Version B3 or B5. B5/S left version - B5/D right version.

TECHNICAL DATA

Input voltage ac	230Δ/400Y
IP class	IP67
Nominal speed	10 rpm
Nominal torque	81,2 Nm
Output power	130 W
Rated current	0.65Δ/0.38Y A
Ratio	285:1



B3

	A	B	C	D	E	F	G	H	H1	K	L	M	N	P	Q	R	S	U	V	W	X	Y	Non Dotted Pitch Pitch H ₁	
PCE44T2	100	80	16	24	50	8	27	80	56	9	259	135	127	67	93	25	M8	28	149	1	15	80	54	8,270
PCE44T2	100	80	16	24	50	8	27	80	56	9	261	135	127	67	130	25	M8	28	171	1	15	80	65	13,870

4D model selection



Electric motor

11.06.2017



Sensored motor

11.06.2017



Worm gearmotors

11.06.2017



Brushless servomotors

11.06.2017



Clean products

11.06.2017



Direct

11.06.2017

Please see product description above for 2D and 3D drawings