

## MINIMOTOR - PC WORM GEAR MOTOR

PC240M3B3-400

230V 1 ph 400rpm 3.3Nm B3 mount

- Single or three phase
- 44 to 270W delivered power
- Up to 20Nm rated torque
- B3 foot or B5 flange mounting
- IP65 as standard



### PRODUCT DESCRIPTION

High quality, designed from the ground up to IP65 rated compact gear motor.

Physically smaller than the majority of similar powered gear motors due to the use of high quality components in precision manufacturing.

Ideally suited to many applications, including label and packaging machines, conveyors, pharmaceutical and medical machinery



**MOTOR:** Asynchronous single or three phase with 2 or 4 poles, totally enclosed with external ventilation. Thermal safety cutout on single phase model. Class F winding. IP65 protection according to CEI EN 60529.

**GEAR UNIT:** Die-cast aluminium casing. Centre distance 32 mm. CARO bronze ring 120-160 HB hardness. Hardened steel screw with ground thread rotating on ball and roller bearings. Lubrication with special long life oil. Sealing rings made in special rubber for high temperatures. 9 gear ratios (i) available, from 7 to 100. Rated torque 20 Nm. Version B3 or B5. B5/S left version - B5/D right version.

[Please click here for 2D and 3D drawings](#)

### TECHNICAL DATA

Capacitor	8 $\mu$ F
Input voltage ac	230V
IP class	IP65
Nominal speed	400 rpm
Nominal torque	3,3 Nm
Output power	140 W
Rated current	1.03A A
Ratio	7:1



3D model selection



Electric motor

15.06.2017



Sensored motor

15.06.2017



Worm gearmotor

15.06.2017



Brushless servomotor

15.06.2017



Clean products

15.06.2017



Direct

15.06.2017

Please see product description above for 2D and 3D drawings

**B3**

Type	A	B	C	D	E	F	G	H	I	L	M	N	P	Q	R	S	T	U	V	X	Height
PC-M3	52	48	58	14	6,5	5	16,3	39	32	236	119	60	68	95	M5	61	56	5	80	60	4.070
PC-M4	52	48	58	14	6,5	5	16,3	39	32	266	119	60	68	95	M5	61	56	5	80	60	5.020