

MINIMOTOR - PA - COAXIAL GEAR MOTOR

PA180M2B3-432
230V 1 ph 432rpm 1.3Nm B3 mount

- Single or three phase
- 34 to 180W delivered power
- Up to 20Nm rated torque
- B3 foot or B5 flange mounting
- IP65 as standard



PRODUCT DESCRIPTION

High quality, designed from the ground up to IP65 rated compact gear motor.

Physically smaller than the majority of similar powered gear motors due to the use of high quality components in precision manufacturing.

Ideally suited to many applications, including label and packaging machines, conveyors, pharmaceutical and medical machinery


MOTOR: Asynchronous single or three phase with 2 or 4 poles, totally enclosed, with External ventilation. Thermal safety cutout on single phase model. Class F winding. IP65 protection according to CEI EN 60529.

GEAR UNIT: Casing in die - cast aluminium. Case - hardened and hardened gear pairs with shafts rotating on roller bearings. Lubrication with long life oil. Sealing rings made in special rubber for high temperatures. 14 gear ratios (i) available, from 6.48 to 372.8. Rated torque 20 Nm. Version B3 or B5.

[Please click here for 2D and 3D drawings.](#)

TECHNICAL DATA

Capacitor	5 μ F
Input voltage ac	230V
IP class	IP65
Nominal speed	432 rpm
Nominal torque	1,3 Nm
Output power	82 W
Rated current	0.68A A
Ratio	6.48:1



B3

Motor Type	A	B	C	D	E	F	G	H	K	L	L1	N	O	R	S	T	V	X	X1	Y	Y1	Y2	W	Z	Z1	Price Standard Product Per kg
PA_M2	89	75	33	14	30	5	16	56	5,5	286	256	64	65	100	M5	13	71	80	60	21	64	9	1,5	56	60	4,215
PA_M3	89	75	33	14	30	5	16	56	5,5	311	281	64	65	100	M6	13	71	80	60	21	64	9	1,5	56	60	4,940

3D model selection



Electric motor

11.06.2017



Gearbox motor

11.06.2017



Worm gearmotors

11.06.2017



Brushless servomotors

11.06.2017



Clean products

11.06.2017



Direct

11.06.2017

Please see product description above for 2D and 3D drawings