


0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

GBAT CYLINDRICAL FUSE LINKS



- Available in 14×51 and 22×58 sizes
- Rated current between 2A to 80A
- Rated voltage of 600V DC
- Ideal for battery protection



PRODUCT DESCRIPTION

gBat Cylindrical fuse links, compliant with the IEC60269-7 Standard, are designed to safeguard battery systems. These fuse links offer comprehensive protection by quickly clearing overcurrents, overloads, and short-circuits, ensuring the safety of batteries, cables, and all associated switchgear installations.

gBat fuse links exhibit rapid operation during short-circuits and maintain reliable performance through continuous charge/discharge cycles. The design optimisation results in reduced power dissipations, enabling their versatile use across a broad spectrum of fuse bases, disconnectors, and fuse-switch disconnectors.

The gBat Cylindrical fuse links range is available in 14×51 and 22×58 sizes and include rated currents from 2A to 80A, and a rated voltage of 600V DC. These fuse links come in standard versions and striker versions and are compatible with fuse bases featuring microswitches.

TECHNICAL DATA

GENERAL DATA

Frequency	4262Hz
Voltage dc max	600 V
Breaking capacity	50 kA
Туре	gBat
Indicator	No
Rated current	2 A
Size	14x51 mm

ADDITIONAL DATA

10



Tariff code	85361010
Weight	18 g
Country of origin	ES