


**3 WIRE INITIATOR TERMINALS - FIK
2.5MM²**

FIK

3295.2

FIK 2.5/3, 2.5mm² Initiator terminal

- Ideal for wiring sensors and actuators
- Pluggable cross connectors
- Easy to assemble
- Flexible marking options

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Rated impulse voltage	4 kV
Colour	Beige
Rated wire cross section	2,5 mm ²
Rated voltage IEC	250 V
Mounting	TS 35
Contamination degree	3
Rated current IEC	24 A
Approvals	EAC
Overvoltage category	III

DIMENSIONS

Height TS 35/7.5	48 mm
Length	72 mm
Width	5,1 mm
Height	47 mm

CONNECTION DATA

Cross connect channels	3
Cross section stranded wire to	4 mm ²
Cross section single wire from	0,2 mm ²
Connections	4
Cross section stranded wire from	0,2 mm ²
Rated wire cross section to (AWG)	12
Rated wire cross section from (AWG)	26
Cross section stranded with ferrule from	0,2 mm ²
Cross section stranded with ferrule to	2,5 mm ²
Stripping length	12 mm
Cross section single wire to	4 mm ²
Number of levels	1
Plug gauge acc. EN 60 947-1	A3

MATERIALS

Flammability class	UL94-V0
Operating temperature from	-40 °C
Operating temperature to	120 °C
Insulation material	Polyamide 6.6

APPROVALS

EAC test standard	TR ZU 004/2011
-------------------	----------------

ADDITIONAL DATA

Pack size	100
Country of origin	BG
Tariff code	85369010
Weight	12,5 g