

SAMOA 1/4" PNEUMATIC DIAPHRAGM PUMP

Non-Metallic

DC20P-BYT-PTT-BAS
DC20, AODD Pump, 1/4", Polypropylene, Telfon, 20 LPM, ATEX

- Pump Size 1/4"
- Connection Types - BSP, Center Ports
- Max. Flow Rate 20 LPM
- Operating Pressure 1.5 - 7 bar



PRODUCT DESCRIPTION

TECHNICAL DATA

| | |
|--|--------------------------|
| Approvals | UKCA, EAC, CE ATEX |
| Country of origin | Spain |
| Diaphragm Type | Overmoulded |
| Fluid Displacement Per Cycle | 0.06 litres |
| Fluid Port Connection Type | BSP Center Ports |
| Material Air Section (Central Body & Air cover) | Polypropylene |
| Material Of Diaphragm | PTFE |
| Material of valve ball | PTFE |
| Material of valve seats | Polypropylene |
| Material of wetted parts | Conductive Polypropylene |
| Max suction lift - Dry | 2 m |
| Max suction lift - Wet | 7 m |
| Max. Flow Rate | 20 LPM |
| Max. Size Of Suspended Solids | 2 mm |
| Net Dimensions | 142mm x 142mm x 173mm |
| Net Weight | 1,2 kg |

| | |
|---------------------------|----------------|
| Operating Pressure | 1.5 - 7 bar |
| Pump size | 1/4" |
| Pump type | Non-Metallic |
| Tariff code | 8413508090 |
| Type | Key Model Pump |