

## SAMOA 1" PNEUMATIC DIAPHRAGM PUMP

Metallic / Non-Metallic

UP10B-CBS-PMA  
UP10, AODD Pump, 1", Polypropylene, Santoprene,  
200 LPM, ATEX

- Pump Size 1"
- Connection Types - BSP/NPT, Side/Center/Multiple Ports, ANSI/DIN Center/Side Flange
- Max. Flow Rate 130-200 LPM
- Operating Pressure 1.5 - 7 / 1.5 - 8 bar



### PRODUCT DESCRIPTION

### TECHNICAL DATA

Approvals	UKCA, CE
Country of origin	Spain
Diaphragm Type	Convolutad
Fluid Displacement Per Cycle	0.85 litres
Fluid Port Connection Type	ANSI/DIN, Central Flange
Material Air Section (Central Body & Air cover)	Conductive Polypropylene
Material Of Diaphragm	Santoprene
Material of valve ball	Santoprene
Material of valve seats	Polypropylene
Material of wetted parts	Conductive Polypropylene
Max suction lift - Dry	5 m
Max suction lift - Wet	8 m
Max. Flow Rate	200 LPM
Max. Size Of Suspended Solids	6,4 mm
Net Dimensions	425mm x 243mm x 415mm
Net Weight	12 kg

<b>Operating Pressure</b>	1.5 - 7 bar
<b>Pump size</b>	1"
<b>Pump type</b>	Non-Metallic
<b>Tariff code</b>	8413508090
<b>Type</b>	Key Model Pump