

FUSE MODULES SM

SM

5712.2

SM 3-E, 3 way Fuse Module, 5 x 20mm fuse - Independent

- Compact TS35/32 Mount
- 3 or 6 Fuse versions
- Screw Connection



PRODUCT DESCRIPTION

The SM fuse modules are designed with three or six mini screw top fuse holders.

Each fuse has its own separate input and output screw PCB terminals.

The fuse holders are design to hold 5 x 20mm fuses.

In the ...G designs, the entries for the fuse holders are connected to each other via the PCB. This allows for a shared power supply.

TECHNICAL DATA

GENERAL DATA

Common feed-in	No
Fuse size	5x20
Number of channels	3

RATINGS

DIN-VDE Spec	DIN VDE 0110 / EN 50178
Current carrying capacity per channel max	4 A
Operating temperature from	-20 °C
Operating voltage ac/dc max	250 V
Operating temperature to	50 °C
Contamination degree	2

Rated current	6,3 A
Overvoltage category	III

DIMENSIONS

Height TS 35/7.5	77 mm
Length	87 mm
Width	24 mm

CONNECTION DATA

Cross section stranded wire to	2,5 mm ²
Cross section single wire from	0,2 mm ²
Cross section stranded wire from	0,2 mm ²
Cross section stranded with ferrule from	0,2 mm ²
Connection type	Screw
Cross section stranded with ferrule to	2,5 mm ²
Stripping length	7 mm
Cross section single wire to	2,5 mm ²
Torque	0,6 Nm

ADDITIONAL DATA

Pack size	1
Country of origin	EEC
Tariff code	85363010
Weight	60,6 g