0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **NXT-D-050 PLANETARY GEARBOX**

Inline direct drive gearbox

NXT-D-050-1-3

- 50mm diameter, high efficiency
- Very high torsional stiffness
- · Low std backlash with tighter tolerance option
- Nominal torque up to 12Nm
- Ratios 3:1 to 81:1



## PRODUCT DESCRIPTION

NXT D series range offers coaxial planetary gearboxes in 4 sizes with high torsional rigidity and standard keyway output shaft.

- Gear ratios from 3:1 (single stage) to 100:1 (two stage)
- Nominal torque handling from 8-110Nm
- Torsional rigidity between 0.7-22Nm/arcmin

Two backlash tolerances are available in each configuration depending on application requirements.

NXT range also includes right-angle and toothed pulley-drive output options, IP65 is standard

## **TECHNICAL DATA**

Axial load max	450 N
Efficiency	96 %
Emergency brake torque	25 Nm
Input speed	3500 rpm
IP class	IP65
Max backlash	8 arcmin
Max radial load	500 N
Max. input speed	6000 rpm
Moment of inertia	0.09 kgcm²
Noise level	70 dB
Nominal torque	8 Nm
Reduction ratio	3
Starting torque	14 Nm
Stiffness	0,8 Nm/arcmin



Weight 0,8 kg