

## DATALOGIC - S5N-PA - STRAIGHT M18 PHOTOELECTRIC SENSOR

S5N-PA-5-T01-PP  
952001271 M18 Transparent Retro PNP M12 Connector



- M18 barrel housing
- Embedded cable or M12 connector
- Flat sides for easy mounting
- PNP or NPN output

### PRODUCT DESCRIPTION

The S5N series of photoelectric sensors offers a wide range of optic functions including, retro reflective, diffuse proximity, background suppression and through beam. They are available with both radial or axial optics and with 2m embedded cable or M12 connection in plastic or metal housing. This sensor offers excellent solutions for all industrial applications, presenting a flat plastic housing with dual fixing holes to guarantee excellent mounting flexibility.

Features & benefits:

- Wide range suitable for all the industrial applications
- Cable or M12 connection
- Flat sides for further mounting options

Applications:

- Automatic machines
- Packaging lines
- Transportation lines
- Automatic warehouses

### TECHNICAL DATA

<b>Approvals</b>	CE, UL
<b>Distance max</b>	1300 mm
<b>Distance min</b>	100 mm
<b>Electrical connection</b>	M12 4-pin connector
<b>Function</b>	Dark on / Light on
<b>IP class</b>	IP67
<b>LED indicator</b>	Yes
<b>Lens material</b>	PMMA
<b>Light type</b>	Red LED

<b>Material of body</b>	PBT
<b>Output</b>	PNP
<b>Output current max</b>	0,1 A
<b>Photocell technology</b>	Retro reflective for transparents
<b>Power consumption max</b>	0,035 A
<b>Reaction time</b>	0,5 ms
<b>Sensitivity setting</b>	Yes
<b>Storage temperature max</b>	70 °C
<b>Storage temperature min</b>	-25 °C
<b>Supply voltage</b>	10-30 V DC
<b>Temperature operational max</b>	55 °C
<b>Temperature operational min</b>	-25 °C
<b>Type of light</b>	LED
<b>Weight</b>	25 g

