

DATALOGIC - S5N-MR - 90° M18 PHOTOELECTRIC SENSOR

S5N-MR-5-T01-PP
952021391 M18 Transparent Retro Metal Radial PNP
M12 Connector

- M18 barrel housing
- Embedded cable or M12 connector
- IP67 Nickel plated brass housing
- PNP or NPN output



PRODUCT DESCRIPTION

The S5N metal series of photoelectric sensors offers a wide range of optic functions including, retro reflective, diffuse proximity, background suppression and through beam. They are available with both radial or axial optics and with 2m embedded cable or M12 connection in a nickel plated brass housing. This sensor offers excellent solutions for all industrial applications.

Features & benefits:

- Wide range suitable for all the industrial applications
- Cable or M12 connection
- Flat sides for further mounting options

Applications:

- Automatic machines
- Packaging lines
- Transportation lines
- Automatic warehouses

TECHNICAL DATA

| | |
|------------------------------|---------------------|
| Approvals | CE, UL |
| Distance max | 1300 mm |
| Distance min | 100 mm |
| Electrical connection | M12 4-pin connector |
| Function | Dark on / Light on |
| IP class | IP67 |
| LED indicator | Yes |
| Lens material | PMMA |

| | |
|------------------------------------|-----------------------------------|
| Light type | Red LED |
| Material of body | Nickel plated brass |
| Output | PNP |
| Output current max | 0,1 A |
| Photocell technology | Retro reflective for transparents |
| Power consumption max | 0,035 A |
| Reaction time | 0,5 ms |
| Sensitivity setting | Yes |
| Storage temperature max | 70 °C |
| Storage temperature min | -25 °C |
| Supply voltage | 10-30 V DC |
| Temperature operational max | 55 °C |
| Temperature operational min | -25 °C |
| Type of light | LED |
| Weight | 60 g |