

QUARTER-TURN 12MM LOCK

2402-022250-2245 Complete 90° lock, 12 mm, Double bit 3, Chrome, assembled

- 12mm lock housing
- IP65
- 90°
- · Vibration resistant
- Compact



PRODUCT DESCRIPTION

Lock housing for vibration-resistant 90° lock.

This variant is structured with a product key, which is resolved together with the product manager.

Lock housing: Zinc, black powder coating.

Mounting: Fork spring

Lock housing variant: square with size 8

Surface coating: chrome

Rule: steel

H/L measurements: 00/45 mm

The clevis spring assembly saves time during assembly and holds the lock securely in place. Intended for plate thickness up to 2.7 mm.

O-ring on the insert and a flat gasket on the lock housing seal the lock.

MATERIAL:

Lock housing: Zinc, chrome-plated or black powder coating, structure.

Insert: Zinc, chrome-plated or black powder coating, structure.

Ruler and screw: Steel, for example. Washer: Stainless steel (304).

Fork spring: Spring steel SS 1774-04, fzb.

TECHNICAL DATA

Configurable	Yes
Dimension H	22 mm
Dimension L	45 mm
Material	Zinc, chrome
Material lock housing	Zinc, chrome
Material rule	Steel
Opening angle	90 °









