



## SUCO 0184/0185 PRESSURE SWITCH STAINLESS STEEL

Stainless steel body

0184457031486  
0,5..5 bar, G1/4, CO, NBR, DIN, Stainless steel

- Up to 250 V
- Connector included (DIN 43650/Form A)
- Five adjustment ranges from 0,5..5 bar to 50..200 bar
- Changeover (SPDT)
- Over pressure safety of 300 bar or 600 bar



### PRODUCT DESCRIPTION

The 0184/0185 series is part of the changeover contact range from SUCO with an integrated plastic body and connector. Offering a maximum voltage of 250 V with a normally open and normally closed contact housed in a hex 27 stainless steel body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include power packs, mobile hydraulics, water systems, hydraulics generally and pneumatics.

### TECHNICAL DATA

<b>Adjustment range max</b>	5 bar
<b>Adjustment range min</b>	0,5 bar
<b>Approvals</b>	CSA US, RoHS II
<b>Contact load max ac</b>	4 A
<b>Contact load max dc</b>	0,25 A
<b>Deviation max</b>	±0,2
<b>Electrical connection</b>	DIN EN 175301-803-A
<b>Function</b>	Changeover (SPDT)
<b>IP class</b>	IP65
<b>Material membrane</b>	NBR
<b>Material of body</b>	Stainless steel
<b>Material of wetted parts</b>	Stainless steel, NBR

Max switching frequency/min	200
Pressure max	300 bar
Process connection	1/4 BSP
Temperature ambient from	-20 °C
Temperature ambient to	80 °C
Temperature of media from	-30 °C
Temperature of media to	100 °C
Weight	130 g
Voltage ac/dc max	250 V
Voltage ac/dc min	10 V

