



SUCO - 0601/0602 PRESSURE SENSOR

Performance series

0601101411002
0-10V, 0..10 bar, G1/4-E, NBR, M12

- Measuring range up to 100 bar
- Ceramic sensor
- Small and compact
- Stainless steel housing



PRODUCT DESCRIPTION

The SUCO 0601/0602 performance series pressure sensor is a small, compact and cost effective pressure monitoring solution. Offering six standard pressure ranges with options of four different electrical connectors a thread of G1/4 and 0-10V or 4-20mA outputs. The 06 series uses a ceramic sensor in thick film technology which is housed in a stainless steel body.

Common applications include mobile hydraulics and power packs.

TECHNICAL DATA

Accuracy	±1% FS
Burst pressure	35 bar
Connection	G1/4-E
Electrical connection	M12x1 4-pole
IP class	IP67
Long term stability	±0.3% FS p.a.
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Ceramic, NBR
Mechanical life expectancy	5 million cycles
Overpressure protection	20 bar
Pressure range max	10 bar
Pressure range min	0 bar

Pressure reference	Gauge
Pressure rise	1 bar/ms
Repeatability	±0.1% FS
Response time	2 ms
Shock resistance	500 m/s ² ; 11 ms half sine wave; DIN EN 60068-2-27
Signal type	0-10 V
Supply voltage dc max	32 V DC
Supply voltage dc min	11 V DC
Temperature ambient from	-30 °C
Temperature ambient to	100 °C
Temperature error	±0.04% FS/°C
Temperature of media from	-30 °C
Temperature of media to	100 °C
Weight	80 g
Vibration resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6



DIN EN 175301-803-A	M 12 – DIN EN 61076-2-101 A	ISO 15170-A1-4.1																																										
<table border="1"> <tr> <td>Pin</td> <td>0601</td> <td>0602</td> </tr> <tr> <td>1</td> <td>U_{v+}</td> <td>U_{v+}</td> </tr> <tr> <td>2</td> <td>Gnd</td> <td>I_{ref}</td> </tr> <tr> <td>3</td> <td>U_{v-}</td> <td>nc*</td> </tr> </table> <p>IP65 x – 60 mm without coupler socket x – 77 mm with coupler socket Order number: 013</p>	Pin	0601	0602	1	U _{v+}	U _{v+}	2	Gnd	I _{ref}	3	U _{v-}	nc*	<table border="1"> <tr> <td>Pin</td> <td>0601</td> <td>0602</td> </tr> <tr> <td>1</td> <td>U_{v+}</td> <td>U_{v+}</td> </tr> <tr> <td>2</td> <td>U_{v-}</td> <td>nc*</td> </tr> <tr> <td>3</td> <td>Gnd</td> <td>I_{ref}</td> </tr> <tr> <td>4</td> <td>nc*</td> <td>nc*</td> </tr> </table> <p>IP67 x – 54 mm Order number: 002</p>	Pin	0601	0602	1	U _{v+}	U _{v+}	2	U _{v-}	nc*	3	Gnd	I _{ref}	4	nc*	nc*	<table border="1"> <tr> <td>Pin</td> <td>0601</td> <td>0602</td> </tr> <tr> <td>1</td> <td>U_{v+}</td> <td>U_{v+}</td> </tr> <tr> <td>2</td> <td>Gnd</td> <td>nc*</td> </tr> <tr> <td>3</td> <td>U_{v-}</td> <td>I_{ref}</td> </tr> <tr> <td>4</td> <td>nc*</td> <td>nc*</td> </tr> </table> <p>IP67, IP69K x – 56 mm Order number: 004</p>	Pin	0601	0602	1	U _{v+}	U _{v+}	2	Gnd	nc*	3	U _{v-}	I _{ref}	4	nc*	nc*
Pin	0601	0602																																										
1	U _{v+}	U _{v+}																																										
2	Gnd	I _{ref}																																										
3	U _{v-}	nc*																																										
Pin	0601	0602																																										
1	U _{v+}	U _{v+}																																										
2	U _{v-}	nc*																																										
3	Gnd	I _{ref}																																										
4	nc*	nc*																																										
Pin	0601	0602																																										
1	U _{v+}	U _{v+}																																										
2	Gnd	nc*																																										
3	U _{v-}	I _{ref}																																										
4	nc*	nc*																																										
<table border="1"> <tr> <td>Pin</td> <td>0601</td> <td>0602</td> </tr> <tr> <td>1</td> <td>U_{v-}</td> <td>nc*</td> </tr> <tr> <td>2</td> <td>Gnd</td> <td>I_{ref}</td> </tr> <tr> <td>3</td> <td>U_{v+}</td> <td>U_{v+}</td> </tr> </table> <p>IP67 x – 61 mm Order number: 007</p>	Pin	0601	0602	1	U _{v-}	nc*	2	Gnd	I _{ref}	3	U _{v+}	U _{v+}	<table border="1"> <tr> <td>Pin</td> <td>0601</td> <td>0602</td> </tr> <tr> <td>A</td> <td>U_{v+}</td> <td>U_{v+}</td> </tr> <tr> <td>B</td> <td>Gnd</td> <td>nc*</td> </tr> <tr> <td>C</td> <td>U_{v-}</td> <td>I_{ref}</td> </tr> </table> <p>IP67, IP69K x – 61 mm Order number: 010</p>	Pin	0601	0602	A	U _{v+}	U _{v+}	B	Gnd	nc*	C	U _{v-}	I _{ref}	<p>Thread code: 41</p>	<p>Thread code: 09</p>																	
Pin	0601	0602																																										
1	U _{v-}	nc*																																										
2	Gnd	I _{ref}																																										
3	U _{v+}	U _{v+}																																										
Pin	0601	0602																																										
A	U _{v+}	U _{v+}																																										
B	Gnd	nc*																																										
C	U _{v-}	I _{ref}																																										