



SUCO - 0183 PRESSURE SWITCH

High pressure

0183462451051

100..300 bar, M14x1.5, CO, NBR, Spade

- Up to 250 V
- Spade terminals
- Two adjustment ranges of 100..300 bar & 200..400 bar
- Changeover (SPDT)
- Over pressure safety of 600 bar



PRODUCT DESCRIPTION

The 0183 series is a high pressure version pressureswitch and is part of the changeover contact range from SUCO. Offering a maximum voltage of 250 V with a normally open and normally closed contact housed in a hex 27 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include power packs, mobile hydraulics, water systems and high pressure systems.

TECHNICAL DATA

Adjustment range max	300 bar
Adjustment range min	100 bar
Approvals	CSA US, RoHS II
Contact load max ac	4 A
Contact load max dc	0,25 A
Deviation max	±10,0
Electrical connection	Spade (AMP 6,3x0,8 mm)
Function	Changeover (SPDT)
Hysteresis	10-30% depending on set value
IP class	IP00
Material membrane	NBR
Material of body	Zinc-plated steel
Material of wetted parts	Zinc-plated steel, NBR

Max switching frequency/min	200
Mechanical life expectancy	1 million exchanges
Pressure max	600 bar
Process connection	M14x1.5
Temperature ambient from	-20 °C
Temperature ambient to	80 °C
Temperature of media from	-40 °C
Temperature of media to	100 °C
Weight	100 g
Voltage ac/dc max	250 V
Voltage ac/dc min	10 V

