

**NON-FLUSH NON-ILLUMINATED  
PUSHBUTTON**

Non Flush Head

L21AB01  
Pushbutton Non Flush Spring Return Red

- IP66 / IP69K
- Spring return or latching
- Optional text or symbol

**PRODUCT DESCRIPTION**

Non flush (projecting) pushbutton heads that mount in a 22.5mm hole with protection rating IP66 / IP69K  
Ideal for applications where an easier activation is required for example when wearing gloves.  
Combine with separate clip and contact blocks to make complete pushbutton assembly.  
Available in multiple colours in spring return or latching.  
Supplied with a matt chrome bezel as standard.  
For black plastic bezel change the part number from L21xxxx to L22xxxx.  
Optional text or symbol can be added please enquire for more details.

**TECHNICAL DATA**

<b>Approvals</b>	UL 508, CSA 22.2, BV, CB, CE
<b>Climatic resistance - constant humid heat</b>	IEC 60068-2-3
<b>Climatic resistance - cyclic damp heat</b>	IEC 60068-2-30
<b>Climatic resistance - sea air</b>	IEC 60068-2-52
<b>Colour</b>	Red
<b>Function</b>	Spring return
<b>Illuminated</b>	No
<b>Impact resistance</b>	IK05
<b>IP class</b>	IP66, IP69, IP69K
<b>Lens colour</b>	Red
<b>Mechanical life expectancy</b>	5 000 000 cycles
<b>Protection class</b>	II (double insulated)
<b>Recommended tightening torque</b>	3 Nm

<b>Storage temperature max</b>	70 °C
<b>Storage temperature min</b>	-40 °C
<b>Temperature operational max</b>	70 °C
<b>Temperature operational min</b>	-25 °C
<b>Type</b>	Non flush pushbutton
<b>Weight</b>	15,8 g

