



BACO®

NON-ILLUMINATED TRIPLE TOUCH

Non Illuminated

L61BA22
Tripletouch Flush Green Arrows Up Down Non Flush
Red Stop

- IP66
- Flush pushbuttons
- Spring return
- Centre projecting button



PRODUCT DESCRIPTION

Non illuminated triple touch heads that mount in a 22.5mm hole with protection rating IP66
The buttons top and bottom are flush with a projecting centre button.

Combine with separate 333E clip and contact blocks to make complete triple touch assembly.
Available in various colour / text / symbol combinations.
All pushbuttons are spring return.

Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L61xxxx to L62xxxx.

Other colour / text / symbol combinations are possible please enquire for more details.

TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Green / red / green
Function	Spring return
Illuminated	No
Impact resistance	IK05
IP class	IP66

Mechanical life expectancy	5 000 000 cycles
Recommended tightening torque	3 Nm
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C
Type	Triple touch

