

## LONG HANDLE ILLUMINATED SELECTOR SWITCH

Long Lever Handle

L21KV30  
Selector Long Handle Illuminated 2 Pos Stable 45°  
Black

- IP66 / IP69K
- 2 or 3 position
- Illuminate with LED blocks
- Black lever with translucent surround



### PRODUCT DESCRIPTION

Illuminated selector switch head with a long lever handle that mount in a 22.5mm hole with protection rating IP66 / IP69K  
Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated selector switch assembly.

The central part of the switch head, side and tip of the lever are translucent and illuminate according to the colour of LED block used.  
The lever of the switch is solid in colour and available only in black.

Available in 2 or 3 position, latching or spring return in various switching angles.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

### TECHNICAL DATA

<b>Angle</b>	45°
<b>Approvals</b>	UL 508, CSA 22.2, BV, CB, CE
<b>Climatic resistance - constant humid heat</b>	IEC 60068-2-3
<b>Climatic resistance - cyclic damp heat</b>	IEC 60068-2-30
<b>Climatic resistance - sea air</b>	IEC 60068-2-52
<b>Colour</b>	Black
<b>Function</b>	Stable
<b>Illuminated</b>	Yes
<b>Impact resistance</b>	IK05
<b>IP class</b>	IP66, IP69, IP69K
<b>Mechanical life expectancy</b>	300 000 cycles

<b>Positions</b>	2
<b>Protection class</b>	II (double insulated)
<b>Recommended tightening torque</b>	3 Nm
<b>Storage temperature max</b>	70 °C
<b>Storage temperature min</b>	-40 °C
<b>Temperature operational max</b>	70 °C
<b>Temperature operational min</b>	-25 °C
<b>Type</b>	Long lever
<b>Weight</b>	17,8 g

