

**SUPER FLUSH NON-ILLUMINATED  
PUSHBUTTON**

Super Flush Head

L23AA01

Pushbutton Super Flush Spring Return Red

- IP66 / IP69K
- Spring return
- Low profile flush mount

**PRODUCT DESCRIPTION**

Super flush pushbutton heads that mount in a 30.5mm hole with protection rating IP66 / IP69K

Ideal for applications where a tamper proof, low profile button is required as only protrudes from front of panel by 2.8mm.

Combine with separate clip and contact blocks to make complete pushbutton assembly.

Available in multiple colours in spring return with a metallic chrome bezel.

Optional text or symbol can be added please enquire for more details.

**TECHNICAL DATA**

<b>Approvals</b>	UL 508, CSA 22.2, BV, CB, CE
<b>Climatic resistance - constant humid heat</b>	IEC 60068-2-3
<b>Climatic resistance - cyclic damp heat</b>	IEC 60068-2-30
<b>Climatic resistance - sea air</b>	IEC 60068-2-52
<b>Colour</b>	Red
<b>Function</b>	Spring return
<b>Illuminated</b>	No
<b>Impact resistance</b>	IK05
<b>IP class</b>	IP66
<b>Mechanical life expectancy</b>	5 000 000 cycles
<b>Recommended tightening torque</b>	3 Nm
<b>Storage temperature max</b>	70 °C

Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C
Type	Super flush pushbutton



