

## KEY HANDLE NON-ILLUMINATED SELECTOR SWITCH

### Key Handle

L21LA00  
Selector Key 2 Position Stable 45° Black 455

- IP66 / IP69K
- 2 or 3 position
- Latching or spring return
- Multiple key profile options



### PRODUCT DESCRIPTION

Non illuminated selector switch head that is key operated and mounts in a 22.5mm hole with protection rating IP66 / IP69K  
Combine with separate clip and contact blocks to make complete switch assembly.

Each head supplied with 2 x keys.

Key profile 455 is standard.

Key profile 1424A available at no extra cost.

Other key profiles available at additional cost please enquire for details.

Available in 2 or 3 position, latching or spring return in various switching angles and key free options.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

### TECHNICAL DATA

<b>Angle</b>	45°
<b>Approvals</b>	UL 508, CSA 22.2, BV, CB, CE
<b>Climatic resistance - constant humid heat</b>	IEC 60068-2-3
<b>Climatic resistance - cyclic damp heat</b>	IEC 60068-2-30
<b>Climatic resistance - sea air</b>	IEC 60068-2-52
<b>Colour</b>	Black
<b>Function</b>	Stable
<b>Illuminated</b>	No
<b>Impact resistance</b>	IK05

<b>IP class</b>	IP66, IP69, IP69K
<b>Key removable</b>	0
<b>Mechanical life expectancy</b>	300 000 cycles
<b>Positions</b>	2
<b>Protection class</b>	II (double insulated)
<b>Recommended tightening torque</b>	3 Nm
<b>Storage temperature max</b>	70 °C
<b>Storage temperature min</b>	-40 °C
<b>Temperature operational max</b>	70 °C
<b>Temperature operational min</b>	-25 °C
<b>Type</b>	Key
<b>Weight</b>	31,2 g

