

KUBLER SERIES 573T IO-LINK POSITION DISPLAY

6.573T.010.E02

- Power supply 18 to 30V DC
- Working temperature -20°C to +60°C
- IP20, IP65
- IO-Link/Modbus
- Touch screen display



PRODUCT DESCRIPTION

The 573T display offers a user-friendly interface, making it easy to configure and operate. The intuitive navigation and clear menu structure simplify setup and customization, allowing users to quickly access the desired settings.

One of the standout features of the 573T display is its versatility. It serves as a multifunctional device, combining the functionalities of a counter, tachometer, and hour meter in one compact unit. This eliminates the need for multiple devices and simplifies the installation process.

The display provides real-time information, allowing for simultaneous monitoring of the actual value and various parameters such as presets, batch numbers, or total sums. This comprehensive display capability enables quick and accurate data interpretation.

The process controller can be used as a simple process converter, process control unit or for complex measuring tasks where 2 values are to be monitored, calculated or further processed.

- Up to 3 display values in one device, display A, display B, calculated display from A and B.
- Simple plain text programming via touch display and separate tare or teach function.
- Mathematical linking of the measured values of input A and B. The result can also be multiplied, divided or added to an offset value to obtain the desired display value.

Key features include:

TECHNICAL DATA

Analogue inputs	2
Analogue outputs	1
Connection	Screw connection
Depth	116 mm
Display	LCD touch display, 13 mm high, 8 decades + sign, 3-colour
IP class	IP20, IP65
Material of body	Plastic

Number of digits	8
Panel size	48x96 mm
Power supply	24 V DC
Supply voltage ac max	230 V AC
Supply voltage ac min	115 V AC
Temperature operational max	60 °C
Temperature operational min	-20 °C
Weight	200 kg
Width	114 mm