


AUTOVIMATION STINGRAY ENCLOSURES

AutoVimation Enclosures For Industrial Cameras

2X.XX8.XXX

Please contact vision@oem.co.uk to help with configuration

- Robust construction
- Vibration-proof
- 90° image rotation
- IP66 rating
- Excellent heat dissipation



PRODUCT DESCRIPTION

SUITABLE FOR CAMERAS:

*The Stingray enclosure is also suitable for all smaller cameras that are not listed here.

- AOS Q-PRI
- AV Bonito Pro
- Avio InfRec TS600
- Basler Runner
- BlueVision BV-C5xxx
- BZB Gear BSHA, BSAHN
- CIS VCC-SXCXP1SW, VCC-20CXP6x
- Dalsa Linea
- Eosens Mini
- Emergent Xtreme, Zenith
- Everet EVZ220
- Fastec HiSpec
- First Light C-Blue, C-Red 2
- Flir A6xx
- HIK CL-Serie (not all types)
- Hitachi HV-HD33
- ICI FMX 320/640
- IDS ueye-WP
- IDT OS, XS
- IFM TOF (with special lid)
- Ikegami ISD-2500HD
- Illunis EMC
- iRayple AX5A22CX050E
- IX Cameras i-SPEED 203, 210, 220
- Jai Spark
- Lucid Helios (with special lid)
- Lumenera Lg11059
- Lumens VC-BC
- Mikrotron Quad, Mini GigE
- Novitec i-Nova3, i-Nova4 Zoom, g-Nova3D
- Optronis CamPerform Cyclone
- Photron Fastcam Mini CX
- Procemex Flex
- Sensors Unlimited 1024-LDM
- SVS Vistek HR
- Vieworks VP
- Vision&Control pictor C300, T300
- Xenics Ceres T 1280, Xeva
- Z3Cam-4K™

• u.v.m.

