

OEM Automatic Ltd Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

HIGH PERFORMANCE FAN HEATER 200 W - 800 W DCR 130

13097.3-16 DCR 130 800W, 56 V DC, internal sensor





- · Integrated adjustable thermostat or hygrostat
- High DC heating performance
- Panel or base mount
- Optical LED indicator



PRODUCT DESCRIPTION

The DCR 130 is a compact DC operated high performance fan heater that prevents the formation of condensation and frost, whilst providing an evenly distributed air temperature inside enclosures.

This fan heater is designed for wall fixing, in addition, the 'DCR 030' offers the same features, but can be mounted directly on the bottom of the enclosure. The plastic housing provides double insulation and acts as protection against direct contact with the heating element.

The DCR range is available with an integrated electronic thermostat or electronic hygrostat, so negates the need for high current switching components. For larger enclosures the DCR range has the option to use a 'plug in' external sensor that can be mounted freely anywhere within the enclosure, they are available in 1m, 2m or 3m lengths.

The external sensor is not included but can be ordered separately. Please see accessories further down the page or see 'external sensors for DCR fan heaters'

TECHNICAL DATA

GENERAL DATA

Mounting	Clip on, Screw fixing
Life span	50,000 h @ +25°C
Nominal voltage	56 V DC
Connection type	2-pole push in connection clamp
Recommended fuse (slow blow)	25 A
Number of fans	1
Heat output	800 W
Air capacity	160 m³/h
Material of body	Plastic
Heater body	Aluminium
DIMENSIONS	

Weight

Depth	179 mm
Width	168 mm
Height	99 mm

SAFETY & APPROVALS

IP class	IP20
Overheating protection	Automatic reset and second tier one shot fuse
Protection class	II (double insulated)
Approvals	CE, cRUus, EAC, RoHS, UL E234324, VDE

RATED OPERATING CONDITIONS

Operational temperature	-20°C +75°C
Control range temperature to	40 °C
Storage temperature	-40°C +80°C
Humidity storage	<90% RH
Operating humidity	< 90% RH
Control range temperature from	-20 °C

Additional information

Thermostat with internal sensor













