

HEATING ELEMENT 15-150W - HG 140

HG

14008.0-00

HG 140 150W Heater, 110-250V ac/dc

- Dynamic heating (PTC element)
- Compact
- Energy saving
- Quick connector and quick installation



PRODUCT DESCRIPTION

The heat source in the element consists of a PTC element – a semi-conductor that adapts its output to the ambient temperature.

The PTC element has a high starting current and provides full output almost immediately. The current then falls quickly and the element is thereafter self-regulating, meaning that the warmer the surroundings, the less output produced by the element.

Thanks to the chimney effect, meaning that the cold air is drawn into the element's bottom and blows out at the top, good self-circulation is achieved for the heated air.

The addition of Pressure Clamp terminals saves time and simplifies the installation.

TECHNICAL DATA

GENERAL DATA

Heat source	Self-regulating PTC-element
Nominal voltage	120-240 V AC/DC
Connection type	3 pressure clamps for stranded wire 0.5-1.5mm ² and rigid wire 0.5- 2.5mm ²
Recommended fuse (slow blow)	10 A
Starting current max	9 A
Heat output	150 W
Mounting	DIN-rail
Heater body	Anodized aluminum

DIMENSIONS

Weight	0,7 kg
--------	--------

Depth	60 mm
Width	70 mm
Height	259 mm

SAFETY & APPROVALS

IP class	IP20
Protection class	I (earthed)
Approvals	CE, EAC, Gost R, RoHS, UL E150057, VDE

RATED OPERATING CONDITIONS

Operational temperature	-45°C ... +70°C
Storage temperature	-45°C ... +70°C
Humidity storage	<90% RH
Operating humidity	< 90% RH
Voltage min	110 V ac/dc
Voltage max	265 V ac/dc
Housing	Anodized aluminium

