

## FAN HEATER 500-700 W HVI 030

03084.0-00

HVI 030 500W Touch-safe fan heater, 230V ac, clip fixing

- Very compact
- Quick mounting for DIN mounting
- High fan capacity
- Heat-insulating protective cover
- Integrated overheat protection



### PRODUCT DESCRIPTION

The HVI030 is a compact and high performance heat exchanger that prevents condensation and frost, and provides evenly distributed internal air temperature within enclosures

Unlike other heat fans, the HVI030 has a relatively large fan that quickly distributes airflow, and thus dries the air efficiently.

The heater fan is fitted with a mounting bracket for DIN mounting or screw mounting. The DIN bracket on the HVI030 has a special design which makes the assembly very fast and easy.

The HVI030 has a modern and functional design. The heat source is double insulated with a plastic casing, which prevents the surface temperature getting too hot. Therefore, the heater can be mounted relatively close to other products in the same application and that you do not have to worry about heat damage

The heater HVI030 is also available without fan if an alternative is preferred.

NOTE: that the heater must always be used with a fan with an airflow of at least 150 m<sup>3</sup> /h free-flowing!

The heater should always be installed together with a regulator (thermostat and/or hygrostat) for best operation.

\* Other operating voltages are available on request.

## TECHNICAL DATA

### GENERAL DATA

<b>Mounting</b>	Clip on, DIN rail
<b>Life span</b>	50 000 h @ +25 °C
<b>Colour</b>	Black
<b>Heat source</b>	Resistor element
<b>Nominal voltage</b>	230 V AC
<b>Connection type</b>	3-pole spring terminal for 2.5 mm <sup>2</sup> cable (1.5 mm <sup>2</sup> with end sleeve)
<b>Recommended fuse (slow blow)</b>	4 A
<b>Number of fans</b>	1

Frequency	50/60 Hz
Heat output	500 W
Air capacity	150 m <sup>3</sup> /h
Material of body	Plastic
Heater body	Plastic

## DIMENSIONS

Weight	1,3 kg
Depth	169 mm
Width	127 mm
Height	89 mm

## SAFETY & APPROVALS

Flammability class	UL94-V0
IP class	IP20
Overheating protection	Overheat protection, fan failure with auto-reset
Protection class	II (double insulated)
Approvals	CE, cULus, EAC, RoHS, UL, UL E234324, VDE

## RATED OPERATING CONDITIONS

Operational temperature	-10°C ... +50°C
Temperature 50 mm above the heater	+75 °C
Storage temperature	-45°C ... +70°C
Humidity storage	<90% RH
Operating humidity	< 90% RH
Voltage min	230 V ac
Voltage max	230 V ac
Fan	Axial fan, ball bearing



