

C16 INDUSTRIAL PCB MOUNT RELAY

C16A25PTL24A

- 2 pole changeover contacts
- 7A switching current
- Din-rail mountable
- Available in AC and DC coil voltages



PRODUCT DESCRIPTION

The C16 relay range is a PCB mount relay featuring 2 changeover contacts.

Key features of the C16 range include:

- AgSnO₂ contact material
- 2 pole changeover contacts
- DIN-Rail Mountable
- Rated to switch up to 7A at 250VAC or 30VDC
- Coil Voltage Options: 12V, 24V, 48V, 110V, 230V (AC/DC variants available)
- 5mm grid

TECHNICAL DATA

INPUT DATA

| | |
|-----------------|------------|
| Working Un | 0,8 - 1,10 |
| Coil voltage ac | 24 V AC |

OUTPUT DATA

| | |
|---------------------------|--------------------|
| Number of contacts | 2 |
| Contact material | AgSnO ₂ |
| Breaking capacity current | 7 A |

| | |
|------------|------|
| Inrush max | 15 A |
|------------|------|

GENERAL DATA

| | |
|-------|-------|
| Width | 13 mm |
|-------|-------|

| | |
|-----------------------------|--------|
| Temperature operational min | -55 °C |
|-----------------------------|--------|

| | |
|-------------------------|--------|
| Storage temperature min | -55 °C |
|-------------------------|--------|

| | |
|-------------------------|-------|
| Storage temperature max | 70 °C |
|-------------------------|-------|

| | |
|-----------------------------|-------|
| Temperature operational max | 70 °C |
|-----------------------------|-------|

| | |
|--------|------|
| Weight | 17 g |
|--------|------|

