

## SOCKETS FOR C9 MINIATURE RELAYS

4-pole

S9M  
Socket For C9 Relay 14 Pin Screw

- DIN-rail or bottom mount
- Semi-protected
- Small construction dimensions, only 22.5 mm wide
- Supplied with open connections
- Retaining bow included



### PRODUCT DESCRIPTION

### TECHNICAL DATA

### OUTPUT DATA

|                           |       |
|---------------------------|-------|
| Breaking Voltage          | 250 V |
| Breaking capacity current | 6 A   |

### GENERAL DATA

|                                     |  |
|-------------------------------------|--|
| Isolation connection/connection     | 2500 V                                     |
| Isolation connection/rail           | 2500 V                                     |
| Material                            | Lexan                                      |
| Torque connection                   | 0,7 Nm                                     |
| Mounting                            | DIN-rail                                   |
| Screw size                          | M3, Pozi                                   |
| Connection area single wire         | 4 mm <sup>2</sup> / 2x2,25 mm <sup>2</sup> |
| Connection area multiple conductors | 0,35-2,5 mm <sup>2</sup>                   |
| Temperature operational min         | -40 °C                                     |
| Storage temperature min             | -40 °C                                     |
| Storage temperature max             | 80 °C                                      |
| Temperature operational max         | 60 °C                                      |
| Weight                              | 54 g                                       |

