

C4 INDUSTRIAL RELAY

4-pole 10 A - MRC

C4-A4024A
Relay 14 Pin 4 Pole 24V ac

- Marking system that can be custom-marked at factory
- Colour-coded test button, both lockable and spring-loaded
- Mechanical indication, double windows



PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Tripping voltage max UN	0,15
Nominal power ac	2,4 VA
Coil voltage ac	24 V AC

OUTPUT DATA

Surge current (20 ms)	30 A
Recommended min load	10 mA/5 V
Bounce time	3
Resistive load 110 V dc max	55 W
Release time	8 ms
Recommended max load	10 A/250 V AC-1; 0,5 A/110 V DC-1
Breaking capacity current	10 A
Release time + contact debounce	9 ms
Breaking Voltage	250 V
Number of contacts	4
Contact material	AgNi
Resistive load 24 V dc max	240 W

GENERAL DATA

Frequency	50 Hz
IP class	IP40
Storage temperature min	-40 °C
Isolation contact/coil	2500 V
Insulation class EN60947	250 V Pollution 3, Group C
Temperature operational max	60 °C
Weight	90 g
Storage temperature max	80 °C
Temperature operational min	-40 °C
Isolation contact/contact	2500 V
Approvals	CCC, Gost R, Lloyd's, CE, RoHS

