

C10 INTERFACE RELAY

1-pole 10 A - IRC

C10A10230A
Relay 5 Pin 1 Pole 230V ac

- Robust flat pins, for industrial applications
- Both mechanical and LED indication
- Colour-coded test button
- Twin contact for low loads



PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Overvoltage UNX max	1,1
Tripping voltage max UN	0,1
Nominal power ac	1,1 VA
Coil voltage ac	230 V AC

OUTPUT DATA


Surge current (20 ms)	30 A
Recommended min load	10 mA / 10 V
Release time	5 ms
Breaking capacity current	10 A
Release time + contact debounce	8 ms
Breaking Voltage	250 V
Mechanical life expectancy	AC:10 Mill./DC:20 Mill
Number of contacts	1
Contact material	AgNi

GENERAL DATA

Frequency	50 Hz
-----------	-------

IP class	IP40
Storage temperature min	-40 °C
Insulation class EN60947	250 V (pollution 3, Group C)
Temperature operational max	70 °C
Storage temperature max	80 °C
Temperature operational min	-40 °C
Approvals	CCC, CE, CSA, Gost R, RoHS, UL
Type of relay	Industrial relay



Gap:
0,5 mm



C10-A10

10A 250V AC-1
10A 30V DC-1

03



A2 —□— A1

CE EAC
Made in India

