

## VALCO - SIDE MOUNT LEVEL SWITCH - S50 SERIES

00.0002.5711

Adj. length, Elbow rod, Brass/SS, 1xCO, Max 25 bar

- PP housing with PG9 electrical connection
- Micro-switch SPDT
- Max working pressure 40 bar
- Max working temperature 180°C
- Brass or St. Steel materials



### PRODUCT DESCRIPTION

These level switches, with their reduced dimensions and simplicity of installation, constitute a reliable solution for the control of liquids in all applications where it is necessary to mount a lateral type. Suitable for use with process temperature up to 180 ° C.

### TECHNICAL DATA

<b>Current</b>	3A
<b>Electrical connection</b>	PG9 cable gland
<b>Function</b>	Changeover (SPDT)
<b>Hysteresis max</b>	20 mm
<b>IP class</b>	IP65
<b>Manufacturer part no.</b>	L1.S50.7.C.25.G.O.W.I33
<b>Material of body</b>	Glass fiber reinforced plastic (PBT)
<b>Material of float</b>	Stainless steel 316
<b>Material of seals</b>	PTFE
<b>Material of wetted parts</b>	Stainless steel
<b>Mounting</b>	Horizontal
<b>Number of microswitches</b>	1
<b>Pressure max</b>	25 bar
<b>Process connection</b>	G1
<b>Rod type</b>	Angled
<b>Specific gravity</b>	0.7
<b>Temperature operational max</b>	180 °C
<b>Voltage</b>	250Vac/48Vdc

