

KUEBLER - ABSOLUTE-CODED ANGULAR TRANSMITTER SENDIX M3663R, MAGNETIC, SSI, Ø36 MM SERIE M3663R

- Housing diameter Ø36 mm
- SSI
- Up to IP69K
- Stainless steel



PRODUCT DESCRIPTION

Sendix M3663R is a magnetically encoded absolute encoder with the latest in multi-color technology with "Energy Harvesting". Energy Harvesting technology is based on magnetic recharging, eliminating both battery and gear.

In addition to multi-color technology, the M3663R has been equipped with extra strong ball bearings and secure attachments, also known as "Safety-Lockplus™".

A unique multifarve pulse sensor with high IP classifications: IP66, IP67 and IP69K, available in stainless steel (V4A).

Please refer to the image below for ordering information.

Order code	8.M3663R.XX2X.XXX2									
Shaft version	Type	a	b	c	d	e	f	g		
a Version										
1 = standard ¹⁾										
clamping flange ø 42 mm [1.65"]										
7 = stainless steel V4A ²⁾										
clamping flange ø 42 mm [1.65"]										
all metal parts accessible from outside are out of stainless steel V4A										
b Shaft (ø x L), with flat										
1 = ø 6 x 12.5 mm [0.24 x 0.49"]										
3 = ø 8 x 15 mm [0.32 x 0.59"]										
5 = ø 10 x 20 mm [0.39 x 0.79"]										
2 = ø 1/4" x 12.5 mm [0.49"]										
E = ø 10 x 20 mm [0.39 x 0.79"], stainless steel V4A										
c Interface / power supply										
2 = SSI / 10 ... 30 V DC										
d Type of connection										
2 = radial cable, 1 m [3.28'] PUR										
B = radial cable, special length PUR *)										
4 = radial M12 connector, 8-pin										
*) Available special lengths (connection type B):										
2, 3, 5, 8, 10, 15 m [5.56, 9.84, 16.40, 26.25, 32.80, 49.21']										
order code expansion .XXXX = length in dm										
ex.: 8.M3663R.132B.G322.0030 (for cable length 3 m)										
e Code										
B = SSI, binary										
G = SSI, gray										
f Resolution (singleturn)										
A = 10 bit ST										
2 = 12 bit ST										
3 = 13 bit ST										
4 = 14 bit ST										
g Resolution (multiturn)										
2 = 12 bit MT										
6 = 16 bit MT										
A = 20 bit MT										
4 = 24 bit MT										
<i>Optional on request</i>										
- Ex 2/22 (only for connection type 4)										
- other shaft diameters out of V4A stainless steel										

TECHNICAL DATA

Connection	Cable, M12
Housing diameter	36 mm
IP class	IP66, IP67, IP69K
Mounting	Shoulder
Output	SSI

Resolution MT	Max. 24 bit
Resolution ST	10-14 bit
Sensor type	Absolute
Shaft diameter max	10 mm
Shaft diameter min	6 mm
Supply voltage dc max	30 V DC
Supply voltage dc min	10 V DC
Temperature operational max	85 °C
Temperature operational min	-40 °C
Version	Multiturn

