



## ADVANCED ILLUMINATION AL150 BALA BAR LIGHT

Broad Area Linear Array

AL150006-660I3  
BALA bar light, 6 LEDs, red 660, strobe/continuous controller



- Designed to handle a long, wide field with low angle of view
- Available in 25 mm (1 ") increments up to 80"



### PRODUCT DESCRIPTION

Designed for applications that require broad illumination over a wide area, or for applications requiring an even broader field of illumination, utilise 2 BALA bar lights in parallel.

The AL150 bar light series is expandable in 1" increments up to 82".

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

Other Wavelength options:

- UV - 395
- Blue - 470
- Green - 520
- Red - 625, 660
- Infrared - 880
- White - WHI

For enquiries or quotes for sizes and power options not listed here please [contact us](#).

## TECHNICAL DATA

### TECHNICAL DATA

<b>Wavelength</b>	660
<b>Colour</b>	Red
<b>Length</b>	41 mm
<b>Width</b>	34 mm
<b>Connector/controller</b>	Strobe/continuous in-line controller
<b>Standard cable length</b>	Up to 2 meters
<b>Photobiological risk factor IEC 6247</b>	Group 1 (low risk)

**Operating temperature** 0°C - 60°C

**Approvals** IEC 62471, CE, RoHS

**IP class** IP50

**Number of LEDs** 6

