

OEM Automatic Ltd Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ADVANCED ILLUMINATION BL 138 SERIES BACK LIGHTS

Expandable High Power Linear Backlights

BL13806-45524

Ai High Power Linear Backlight, 6", Blue, 24V

- 510,000 lux perfect for line-scanning applications
- Available 6" (152.4mm) increments from 6" (152.4mm) to 96" (2438.4mm) with the exception of a 3" (76.2mm)model
- Intensity control of entire light via 0 10v input





PRODUCT DESCRIPTION

The BL138 is a high intensity linear backlight offering 510 kLux output, making this perfect for back-lit, line scanning applications. Available from 6" length up to 96" in increments of 6". A 3" (75mm) length option is also available. Available intensity control provides illuminance adjustability for every 6" increment via a 0 – 10v input.

Power options include:

- C1 connector for use with DCS series controllers
- C5 connector for use with Pulsar 320 strobe controller
- Continuous in-line controller powered by 24V power supply
- Flying/tinned leads powered by 24V power supply

For enquiries or quotes for sizes and power options not listed here please contact us.

TECHNICAL DATA

TECHNICAL DATA

IP class	IP50
Wavelength	455
Colour	Blue
Operating temperature	0°C - 60°C
Standard cable length	Up to 2 meters
Length	152 mm
Photobiological risk factor IEC 6247	Group 1 (low risk)
Width	90,8 mm
Connector/controller	Flying/tinned leads
Approvals	IEC 62471, CE, RoHS