

OEM Automatic Ltd


Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk


ADVANCED ILLUMINATION AL295 MICROBRITE BAR LIGHT

Compact Area Lighting

AL295-150-455C5 Ai MicroBrite™ Bar Light, 150mm, Royal Blue, Pulsar









PRODUCT DESCRIPTION

The AL295 is part of the Microbrite family of high performance, compact machine vision lights. Outperforming the competition with a high intensity output of 73 kLux at a working distance of 100mm. The AL295 is available is expandable sizes in 3" increments up to 18".

Power options include:

- C1 connector for use with DCS series controllers
- C5 connector for use with Pulsar 320 strobe controller
- Continuous in-line controller powered by 24V power supply
- Combination strobe/continuous in-line controller powered by 24V power supply
- Default-OFF strobe/continuous in-line controller powered by 24V power supply
- Flying/tinned leads powered by 24V power supply

Other Wavelength options:

- UV 365, 375, 385, 395, 405
- Royal blue 455
- Blue 470
- Cyan 505
- Green 530
- Amber 590
- Red orange 625
- Red 660
- Infrared 730, 850, 940
- White WHI

For enquiries or quotes for wavelength and power options not listed here please contact us.

TECHNICAL DATA

TECHNICAL DATA

IP class	IP50
Wavelength	455
Colour	Royal blue

Operating temperature	0 - 60°C
Standard cable length	Up to 2 meters
Weight	68,9 g
Length	166 mm
Photobiological risk factor IEC 6247	Group 2 (moderate risk)
Width	20 mm
Connector/controller	C5 connector
Approvals	IEC 62471, CE, RoHS