

Strobe/Continuous Backlight

BL-S100150-470
Ai EuroBrite™ Backlight, Medium, Blue

- Double the size of the BL-S050075
- Cost-effective, feature-rich design
- On-board smart driver - seamless strobe or continuous
- IP67 enclosure



PRODUCT DESCRIPTION

With complete built-in control for continuous and strobe modes, the Eurobrite™ range outdoes the competition in many ways. One major feature of the Eurobrite™ is Adaptive Power™ which utilizes an onboard thermistor to maximize light output in continuous mode. As well as Adaptive Power™ to provide maximal output pulse in strobe mode regardless of the exposure period.

Additional features:


- IP67 sealed enclosure suitable for washdown environments
- Rugged construction that has been tested to withstand over 1000lb
- Industrial grade LEDs providing high-intensity surface illumination of 38klux

For other wavelength options not listed here please [contact us](#).

TECHNICAL DATA


TECHNICAL DATA

IP class	IP67
Wavelength	470
Colour	Blue
Operating temperature	0°C - 60°C
Standard cable length	No cable included, use standard coded 5-pin M12
Weight	254,1 g
Length	150 mm
Photobiological risk factor IEC 6247	Group 1 (low risk)
Width	139 mm
Connector/controller	Strobe
Approvals	IEC 62471, CE, RoHS



Length (mm)	150
Width (mm)	139
Height (mm)	30

Dimensions are in millimeters



Length (mm)	150
Width (mm)	139
Height (mm)	30

Dimensions are in millimeters