

**MOLEX - MPM M8/M12-DIN A / DIN B  
INDUSTRIAL MOULDED CABLE  
CONNECTORS**E85000P12M006  
DINA-M12 0,6m PUR-cable 0-250 V

- Fully overmoulded for better protection
- Quick and simple installation with M8 and M12
- With or without LED and transient protection
- EN175301-803 (DIN43650)-M8 / M12

**PRODUCT DESCRIPTION**

DIN Valve Connectors with moulded cable, IP65 rated. IP67 version available on request.

**TECHNICAL DATA**

<b>Cable length</b>	0,6 m
<b>Circuit</b>	No circuit
<b>Colour cable</b>	Black
<b>Connection - male</b>	M12
<b>Connector</b>	DINA 43650
<b>Contact head 1</b>	DIN
<b>Current max</b>	3 A
<b>IP class</b>	IP65
<b>LED indicator</b>	No
<b>Material cable</b>	PUR/PVC
<b>Rated wire cross section</b>	0,5 mm <sup>2</sup>
<b>Temperature range fixed use from</b>	-40 °C
<b>Temperature range fixed use to</b>	90 °C
<b>Temperature range flexible use from</b>	-15 °C
<b>Temperature range flexible use to</b>	90 °C
<b>Voltage ac/dc max</b>	250 V

